

**NEW & REPLACEMENT CONCRETE
VARIOUS LOCATIONS – NORTH PENN SCHOOL DISTRICT**

1. Intent of Bid Specifications

The North Penn School District solicits bids for new and replacement concrete requirements for 2018-2019. Work on the proposed projects will be done as required for the period from July 1, 2018 through June 30, 2019. Each bid will be based on a per square foot or a per lineal foot price for the specified concrete work to be completed. The unit priced concrete could be performed at any of the following North Penn School District facilities:

North Penn High School 1340 Valley Forge Road Lansdale, PA 19446	Bus Garage 1340 Valley Forge Road Lansdale, PA 19446	Northbridge School 2374 North Penn Road Hatfield, PA 19440
Pennbrook Middle School 1201 East Walnut Street North Wales, PA 19454	Penndale Middle School 400 Penn Street Lansdale, PA 19446	Pennfield Middle School 726 Forty Foot Road Hatfield, PA 19440
Bridle Path Elementary 200 Bridle Path Road Lansdale, PA 19446	Gwyn-Nor Elementary 139 East Hancock Road North Wales, PA 19454	Gwynedd Square Elem 1641 Supplee Road Lansdale, PA 19446
Hatfield ES 1701 Fairgrounds Road Hatfield, PA 19440	Inglewood Elementary 1313 Allentown Road Lansdale, PA 19446	Knapp Elementary 698 Knapp Road Lansdale, PA 19446
A. M. Kulp Elementary 801 Cowpath Road Hatfield, PA 19440	Montgomery Elementary 1221 Stump Road North Wales, PA 19454	General Nash Elementary 1560 Liberty Bell Drive Harleysville, PA 19438
North Wales Elementary 201 Summit Street North Wales, PA 19454	Oak Park Elementary 500 Squirrel Lane Lansdale, PA 19446	Walton Farm Elementary 1610 Allentown Road Lansdale, PA 19446
York Avenue Elementary 700 York Avenue Lansdale, PA 19446	Educational Service Center 401 East Hancock Street Lansdale, PA 19446	Support Services Center 630 West 8 th Street Lansdale, PA 19446

2. Scope of Work/Specifications

- A. The successful bidder will be required to provide all necessary labor, materials, equipment, supervision and transportation to perform new concrete installations, concrete replacements and concrete curb replacements in accordance with these specifications.
- B. In areas designated by the Facilities Department, all existing concrete shall be removed. All debris including reinforcing wire and broken concrete shall be removed from the job site by the contractor. It is important that sidewalk blocks be removed at expansion or scored joints. Scored joints should be carefully sawed so that the new cast-in-place concrete establishes a smooth transition to existing sidewalks and curbs.

NORTH PENN SCHOOL DISTRICT
NEW & REPLACEMENT CONCRETE 2018-19

- C. All voids or soil erosion found after removal of deteriorated concrete must be filled in with No. 2A crushed stone and compacted to provide a firm foundation for the new concrete.
- D. All forms used shall be of a uniform width for sidewalks. All sidewalks shall be the same width as existing. Provide form materials with sufficient stability to withstand pressure of placed concrete without bow or deflection.
- E. Joint fillers for expansion joints shall be asphalt impregnated pre-molded type. Expansion joints required in all areas will be placed prior to pouring.
- F. Reinforcing wire shall be a minimum of #10 gauge – 6” x 6” mesh for all sidewalk replacement. Install welded wire fabric in as long of length as practicable, lapping at least one mesh.
- G. Design mixes shall provide normal weight concrete with the following properties:
- 4000 PSI 28 day compressive strength
 - W/C ratio 0.58 maximum (non-air entrained)
 - W/C ratio 0.46 maximum (air entrained).
- H. Ready mixed concrete shall comply with requirements of ASTM C94. During hot weather, or under conditions contributing to rapid setting of concrete, a shorter mixing time than specified in ASTM C94 may be required. When air temperature is between 85 degrees F and 90 degrees F, reduce mixing and delivery time from 1 ½ hours to 75 minutes, and when air temperature is above 90 degrees F, reduce mixing and delivery time to 60 minutes. Above time may be increased if a retarding mixture is used.
- I. Mix certificates: Delivery tickets signed by concrete producer and contractor shall be submitted to the owner’s representative.
- J. A minimum of 4” of concrete shall be poured in place for all sidewalks. Deposit concrete continuously so that no concrete will be placed on concrete, which has hardened sufficiently to cause the formation of seams or planes of weakness. All pours shall be carried on at such a rate that the concrete will remain loose enough to flow readily into all areas and corners. Reinforcing wire shall be lifted to the center of the 4” thickness.
- K. Soon after screeding and while the concrete is still pliant, the surface is to receive a trowel finish. Immediately, after trowel finishing, slightly roughen the concrete surface by brooming with a fiber bristle broom perpendicular to the main traffic route. Coordinate the required final finish with owner’s representative before application.
- L. NOTE: In all areas where replacement concrete abuts against existing concrete sidewalks and curbs, holes shall be drilled 15” on center and 3” deep to accept # 6 rebar, 6 inches in length. This procedure is used throughout the school district to prevent the settling of sidewalks, thus eliminating trip hazards.

NORTH PENN SCHOOL DISTRICT
NEW & REPLACEMENT CONCRETE 2018-19

- M. NEW SIDEWALKS: Where new sidewalks are to be installed, the contractor shall excavate to a depth of 8 inches and backfill with 4 inches of 3/4 inch, clean, compacted stone before pouring new concrete.
 - N. After forms have been removed from the sidewalks, the existing voids on either side of the new walk shall be backfilled and graded to conform to the existing grades before sidewalks were replaced. Dirt areas shall be seeded with a turf grass seed.
 - O. REPLACEMENT CURBING: Where existing curbing is to be removed and replaced, the Contractor shall back-cut macadam to the minimum width necessary to remove curb and shall back-fill after pour with 3/4 inch clean stone. Macadam repair will be done by others.
 - P. Curbing shall be constructed in ten (10) foot lengths and have the appropriate expansion materials installed according to PennDOT specifications. All curbing shall match existing unless otherwise instructed.
 - Q. All concrete shall be protected from premature drying and excessive cold or hot temperatures. Comply with ACI 306.1 for cold weather protection and with recommendations in ACI 305R for hot-weather protection during curing.
 - R. All new concrete shall be sealed in accordance with sealer manufacturer's written instructions. Maintain continuity of coating and repair damage during curing period.
 - S. Contractor shall be responsible for the disposal of all removed concrete, extra dirt, and all detritus by the end of the job.
 - T. All work areas must be clearly marked and/or barricaded during this project. Precautions must be taken to ensure pedestrian safety. Any and all damage to other lawn areas must be restored at the conclusion of the project.
 - U. The contractor shall guarantee all work for a period of one (1) year from the date of acceptance.
 - V. Final square footage totals will be determined by mutual agreement of the contractor and owner's representative.
3. Safety
- A. Safety of students, staff and visitors is paramount in executing this contract. The contractor should never compete with school activities to continue/complete his work. If necessary, this contractor will return to occupied areas after normal working hours.
 - B. All work under this contract must follow ALL state and federal environmental rules and regulations.
4. Project Continuance

The District may approve multiple concrete projects during the 2018-2019 school year and this specification and unit costs are to remain in effect from July 1st, 2018 until June 30th, 2019.

NORTH PENN SCHOOL DISTRICT
NEW & REPLACEMENT CONCRETE 2018-19

5. Information Contact

Any questions regarding this specification or project work may be referred to:

Scott Kennedy
Director of Facilities & Operations
North Penn School District
630 W. Eighth St.
Lansdale, PA 19446
Tel. 215-853-1140

6. **Completing the Sealed Bid – Due by 2:00 pm on Thursday May 17, 2018**

Bid proposals shall be sent to the North Penn School District Support Services Center **630 W. Eighth St., Lansdale, PA 19446. Attention: Scott Kennedy**

All bids shall be clearly marked on the envelope:

“SEALED BID – NEW & REPLACEMENT CONCRETE – 2018-2019”

NOTE: The North Penn School District Board of School Directors reserves the right to award all or any portion of this bid at its sole discretion.

CLEARANCES: The successful Bidder must supply to North Penn School District documentation required by Act 34, Section III of the Public School Code (Criminal Record Check) and Act 151, Chapter 63 of 23 PA Consolidated Statutes (Pennsylvania Child Abuse History Clearance) and Act 114 (FBI Fingerprinting Clearances) before work on a project shall begin. These forms must be current for every worker on site at all times.

Contractor must enclose a copy of their current commercial liability insurance certificate with your proposal.

All bidders must complete the attached Non-Collusion Affidavit.

**NORTH PENN SCHOOL DISTRICT
LANSDALE, PA 19446-3960**

BID PROPOSAL FORM

New & Replacement Concrete 2018-2019

We, the undersigned have reviewed the specifications herein for New & Replacement Concrete and propose to furnish all labor, equipment, & materials, where applicable to complete the work strictly in accordance with the attached specifications, terms and conditions as set forth in the attached instruction to bidders.

Replacement Sidewalks:

Cost per square foot: \$ _____

New Sidewalks:

Cost per square foot: \$ _____

Replacement Curbing:

Cost per lineal foot: \$ _____

We understand that the North Penn School District reserves the right to reject any and all bids and make awards on the basis of contractor qualifications as well as price.

Name of Company

Authorized Signature

Street Address

City

State

Zip Code

Date

Telephone Number

Fax Number

North Penn School District
Lansdale, Pennsylvania 19446-3807

Non-Collusion Affidavit

Instructions:

1. This Non-Collusion Affidavit is material to any contract awarded pursuant to this bid. According to the Pennsylvania Antibid-Rigging Act, 73 P.S. 1611 et sec., governmental agencies may require Non-Collusion Affidavits to be submitted together with bids.
2. This Non-Collusion Affidavit must be executed by the member, officer or employee of the bidder who makes the final decision on prices and the amount quoted in the bid.
3. Bid rigging and other efforts to restrain competition, and the making of false SWORN statement in connection with the submission of bids are unlawful and may be subject to criminal prosecution. The person who signs the Affidavit should examine it carefully before signing and assure himself or herself that each statement is true and accurate, making diligent inquiry, as necessary, of all other persons employed by or associated with the bidder with responsibilities for the associated approval or submission of the bid.
4. In the case of a bid submitted by a joint venture, each party to the venture must be identified in the bid documents, and an Affidavit must be submitted separately on behalf of each party.
5. The term "Complementary Bid" as used in the Affidavit has the meaning commonly associated with that term in the bidding process, and includes the knowing submission of bids higher than the bid of another firm, any intentionally high or non-competitive bid, and any other form of bid submitted for the purpose of giving a false appearance of competition.
6. Failure to file an Affidavit in compliance with these instructions may result in disqualification of the bid.

Non-Collusion Affidavit

State of _____ County of _____

I state that I am _____ of _____
(Title) (Name of my Firm)

and that I am authorized to make this affidavit on behalf of my firm, and its Owners, Directors, and Officers. I am the person responsible in my firm for price(s) and the amount of this bid.

I state that:

1. The price(s) and amount of this bid have been arrived at independently and without consultation, communication or agreement with any other contractor, bidder or potential bidder.
2. Neither the price(s) nor the amount of this bid, and neither the approximate price(s) nor approximate amount of this bid, have been disclosed to any other firm or person who is a bidder or potential bidder, and they will not be disclosed before bid opening.
3. No attempt has been made or will be made to induce any firm or person to refrain from bidding on this contract, or to submit a bid higher than this bid, or to submit any intentionally high or non-competitive bid or other form of competitive bid.
4. The bid of my firm is made in good faith and not pursuant to any agreement or discussion with, or inducement from, any firm or person to submit a complementary or other non-competitive bid.

Non-Collusion Affidavit (con't.)

5. _____, its affiliates, subsidiaries, officers, directors, and employees are not currently under _____ (name of my firm) investigation by any governmental agency and have not in the last four years been convicted or found liable for any act prohibited by State or Federal Law in any jurisdiction, involving conspiracy or collusion with respect to bidding on any public contract, except as follows:

I state that _____ understands and acknowledges that the above representations are material and _____ (name of my firm) important, and will be relied on by North Penn School District in awarding the contract for which this bid is submitted. I understand and my firm understands that any misstatement in this affidavit is and shall be treated as fraudulent concealment from the North Penn School District of the true facts relating to the submission of bids for this contract.

(Name)

and

(Company Position)

SWORN TO AND SUBSCRIBED

BEFORE ME THIS _____ DAY

OF _____, 20____.

Notary Public

My Commission Expires